

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	CAST SPA
Address	Strada Brandizzo 404, Volpiano (To), 10088, Italy
Type	Compression Fittings
Description	Carbon steel and stainless steel pipe couplings, cutting ring types for B3 without and B4 with double elastomer seal (NBR or Viton) for L & S pipe series.
Trade Name	B3 and B4
Application	General use in piping systems on ships classed or intended for Classification with Lloyd's Register, where the rotary flexure test is not required. <u>Restrictions for B4 cutting ring:</u> <ol style="list-style-type: none">1. Starting/control air and CO2 systems.2. Inside machinery spaces of category A or accommodation spaces for main lines of inert gas systems.3. Water spray or sprinkler systems which are not always filled with water.4. Scupper pipes below freeboard deck over board
Specified Standard	LR Rules and Regulations for the Classification of Ships, 2020

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Torsten Schroeder

Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Ratings

Type	Sizes (mm)	Pressure (bar)
L-Series (light)	6 to 42	315 to 160
S-Series (heavy)	6 to 38	630 to 315
Temperature range: -20°C to 120°C (carbon steel)		
-60°C to 200°C (stainless steel)		

Other Conditions

Selection and installation of couplings have to be in accordance with manufactures recommendations and instructions.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document No. HTS/ENS 32446-15, Issue 1 and its supplementary Type Approval Terms and Conditions form part of this Certificate.